


HVR True Series

Diode-free : Interior/Exterior : IP65




Date: _____ Project: _____ Type: _____


| Model Number | HVRT-XX-HO | |
|----------------------------|------------|-----|
| Lumens/foot | 2700K | 270 |
| | 3000K | 275 |
| | 4100K | 295 |
| Watts/foot | 4 | |
| Power factor | > 0.90 | |
| Cut section length | 12" | |
| Diode spacing (pitch) O.C. | - | |
| Diodes per foot | - | |
| Maximum run length | 164' | |




Mounting clip




EXT-DWC-4




EXT-DWS-4



EXT-SNL-4



EXT-PNL-4



Rotating clip

Ordering Guide:

| HVRT | CCT | Output/Foot | Length | Mounting |
|------|--|--------------|--------------------------------------|--|
| HVRT | 27 (2700K) 30 (3000K) 41 (4100K) | HO (4 watts) | CC @XX (custom cut, specify footage) | MC (Mounting clip) DWC (EXT-DWC-4) DWS (EXT-DWS-4) SNL (EXT-SNL-4) PNL (EXT-PNL-4) - RC (to add rotating clip to channel) |

HVR series ribbon is 120VAC, requiring all lengths, lead wire, & jumpers to be made in our factory in order to maintain the ETL listing. Lead times apply.

