

TRUE MICRO SERIES

INTERIOR RIBBON & CHANNEL




Date: _____ Project: _____ Type: _____

TRUE MICRO SERIES RIBBON

Ordering Guide:

Series	-	CCT	-	Output/Foot	-	Length
TRUM	-	27 (2700K) 30 (3000K) 41 (4100K)	-	HO (3.05watts)	-	CC @XX (custom cut, specify footage)



* True Micro must be mounted in channel

Note: Drawings not to scale.

Features:

- 170° beam angle
- Narrow ribbon design
- 24 Volt
- CRI 90+
- No diode imaging
- Dimmable: ELV,MLV,TRIAC or 0-10V
- Field cuttable
- 50,000 hour life
- 5 year warranty
- IP20



Model Number	TRUM-XX-HO	
Lumens/foot	2700K	285
	3000K	290
	4100K	305
Watts/foot	3.05	
Cut section length	1.79"	
Diode spacing (pitch) O.C.	NA	
Diodes per foot	NA	
Maximum run length	31'	

True Micro series ribbon is available in custom cut lengths only.

All Omnilight products are tested and warrantied for use exclusively with Omnilight power supplies

TRUE MICRO SERIES

INTERIOR RIBBON & CHANNEL





Date: _____ Project: _____ Type: _____

OCH SERIES CHANNEL FOR THE TRUE MICRO SERIES RIBBON



Ordering Guide:

Series	Model	Length	Lens	Channel Finish
OCH	073 116 117	CC (Specify custom length)	FR (Frosted) BK (Black)	AL (Aluminum) BK (Black) WH (White)

OCH-073



OCH-116



OCH-116

